

4 CHANNEL QUAD DVR WITH AUDIO

Wavelet Compression Format Produces Vivid Images

FEATURES | BENEFITS

- Multiplexing & Quad Recording Modes
- 4 Audio Inputs & 2 Audio Outputs
- Live PIP & 2X to 4X Linear Zoom
- Real Time 120 FPS Quad & 30 FPS Full Screen
- Alarm In/Outputs & Video Loss Detection
- Video Motion Detection & Motion Trigger Output
- Choose Hard Drive Size



DVR 4004

SPECIFICATIONS | DVR 4004

VIDEO FORMAT	NTSC/EIA
HARD DISK STORAGE	IDE TYPE, UDMA 66, SUPPORTED 200 GB HDD REMOVABLE
RECORD MODE	MANUAL/ALARM/TIMER/MOTION
CAMERA INPUT SIGNAL	COMPOSITE VIDEO SIGNAL 1 Vp-p 75 Ohm BNC, 4 CHANNELS
MAIN MONITOR OUTPUT	COMPOSITE VIDEO SIGNAL 1 Vp-p 75 Ohm BNC
CALL MONITOR OUTPUT	COMPOSITE VIDEO SIGNAL 1 Vp-p 75 Ohm BNC
AUDIO INPUT	4 AUDIO INPUTS, (RCA)
AUDIO OUTPUT	2 AUDIO OUTPUTS, (RCA)
MOTION DETECT AREA	16*12 TARGETS PER CAMERAS
MOTION DETECT SENSITIVITY	99 LEVELS
VIDEO LOSS DETECTION	YES
REFRESH RATE	UP TO 240 FIELD IMAGES/SEC FOR NTSC
RECORDING RATE	UP TO 30 IMAGES/SEC FOR NTSC
DWELL TIME	PROGRAMMABLE (1~10 SEC)
PICTURE IN PICTURE	YES (MOVABLE)
KEY LOCK	YES
PICTURE ZOOM	2*2~4*4 (MOVABLE)
CAMERA TITLE	8 LETTERS
VIDEO ADJUSTABLE	HUE/COLOR/CONTRAST/BRIGHTNESS ADJUSTABLE
ALARM INPUT	TTL INPUT, Hi (V), Low (GND)
ALARM OUTPUT	COM./N.O
REMOTE CONTROL	RS-232 OR RS-485
TIME DISPLAY FORMAT	YY/MM/DD, DD/MM/YY, MM/DD/YY, OFF
POWER SOURCE	AC90-220V, 47Hz ~63Hz
OPERATION TEMPERATURE	50°F~104°F
RS-232C/RS-485 (bps)	115200,57600,19200,9600,4800,3600, 2400,1200
DIMENSION	13.5"(W) x 8.75"(D) x 2.5"(H)
NET WEIGHT	4.5 Lbs