



www.ktlcctv.com

## 4 CHANNEL NETWORKABLE DVR

Wavelet Compression Format Produces Vivid Images

### FEATURES | BENEFITS

- Multiplexing & Quad Recording Modes
- Network Capability
- 4 Audio Inputs & 2 Audio Outputs
- Live PIP & 2X to 4X Linear Zoom
- Real Time 30 FPS
- Alarm In/Outputs & Video Loss Detection
- Video Motion Detection & Motion Trigger Output
- Single Swappable Drive Bay
- Choose Hard Drive Size



DVR4104N

### SPECIFICATIONS | DVR4104N

Video format	NTSC/EIA	
Resolution	VGA	640 X 480
	QVGA	320 X 240
Hard disk storage	IDE type, UDMA 66, supported more than 250 GB HDD	
Recording mode	Manual / Alarm / Timer / Motion	
Camera Input Signal	Composite video signal 1 Vp-p 75Ω BNC, 4 channels	
Main Monitor Output	Composite video signal 1 Vp-p 75Ω BNC	
Network Interface	Ethernet (10/100 Base-T)	
Protocols	TCP/IP, ICMP, SMTP, HTTP, FTP	
Call Monitor Output	Composite video signal 1 Vp-p 75Ω BNC	
Audio input	4 audio inputs, (RCA) *	
Audio output	2 audio outputs, (RCA) **	
Motion Detect Area	16 * 12 targets per camera	
Motion Detect Sensitivity	99 Levels	
Video Loss Detection	Yes	
Refresh Rate	240 fields/sec. for NTSC	
Recording	Multiplex	Up to 30 fields/sec.<NTSC>
	Quad-field	Up to 120 fields/sec.<NTSC>
	Quad-frame	Up to 240 fields/sec.<NTSC>
Performance via Ethernet	Up to 15 frames/sec(NTSC), 12.5(PAL) frames/sec	
Dwell Time	Programmable (1~15 Sec)	
Picture in Picture	Yes (Movable)	
Key Lock	Yes	
Picture Zoom	2*2 ~4*4 (Movable)	
Camera Title	8 letters	
Video Adjustable	Hue/ Color/ Contrast/ Brightness Adjustable	
Alarm Input	TTL input, Hi (5V), Low (GND)	
Alarm Output	COM./N.O/N.C	
Trigger & Action	E-Mail images or images uploading to FTP site's specific account/Remote Recording	
Time Display Format	YY/MM/DD, DD/MM/YY, MM/DD/YY, OFF	
Power Source	DC 19V	
Power Consumption	<32W	
Operation Temperature	50 DEGREES F ~ 104 DEGREES F	
Dimension	13.5"(W) x 8.75"(L) x 2.3"(H)	
Net Weight	4.4 LBS	

Available at: