

ALL-IN-ONE WEATHERPROOF COLOR CAMERA

Outstanding Value! Camera Weatherproof Housing & Bracket

FEATURES | BENEFITS

- 380 Lines of Resolution
- .1 Lux Light Rating
- 0.00 Lux Light Rating With IR LED's
- Internal Automatic Electronic Shutter
- Built-in AGC & Auto White Balance
- Compact 2.75" Diameter x 4" Length.
- Built-in Sun Shield & Mounting Bracket
- Infrared Illumination Range of 40'
- EZ-Connect Video/Power Cable
- Smart Electronic Photo Cell for IR LED's
- Power 12VDC 130ma or 170mA w/ LED's



SPECIFICATIONS | CFC6019IR

IMAGE SENSOR DEVICE	SONY CCD 1/3" INTERLINE
PIXEL NUMBER TOTAL	537(H) X 505(V)NTSC
EFFECTIVE	510(H) X 492(V)NTSC
SCANNING STANDARD	2:1 INTERLACE NTSC STANDARD 525 LINES, 30 FPS AL STANDARD 625 LINES, 25FPS
SHUTTER CONTROL	AUTO 1/60-1/100,000
SYNCHRONIZING SYSTEM	INTERNAL
HORIZONTAL RESOLUTION	380 TV LINES
ELECTRONIC SHUTTER CONTROL	AUTO SHUTTER, 1/60-1/100,000 NTSC
GAMMA CORRECTION	0.45
MINIMUM ILLUMINATION	0.1 LUX/F1.2, IR ON: 0 LUX
VIDEO OUTPUT LEVEL	1 VP-P/75 OHMS, COMPOSITE
VIDEO S/N RATIO	48 dB (AGC OFF)
WHITE BALANCE	AUTO (2,000 XK - 10,000 XK)
BACKLIGHT COMPENSATION	AUTO
OPERATING TEMPERATURE	14°F - 122°F
STORAGE TEMPERATURE	-22°F - 176°F
POWER REQUIREMENT	DC 12V, 10%
TOTAL	DC12V 250mA
CAMERA	DC12V 130mA
IR LED PROJECTING LIGHTER	DC12VmA
RANGE OF DISTANCE	40'
LENS STANDARD	6mm
DIMENSIONS	6.5"(L) X 3.5"(W) X 5.5"(H)