

# SPECIFICATIONS

## ●Camera

Effective Pixels	660 (H) x 492 (V)
Lens	F2.35 Horizontal Angular field of view: 51° Focal length: 50 cm ~ ∞
Minimum Illumination:	10 lx (1 foot-candle) (30 fps, Slow shutter: OFF) 2 lx (0.2 foot-candle) (Sensitivity up: 10 is selected)
Panning range	140° (-70° - +70°)
Tilting range	120° (-90° - +30°) when mounted on the wall
Pan / Tilt Preset Positions	8 positions

## ●Other Specifications

Power Source	9V DC, 330mA (using the supplied AC adapter)
Power Source (Supplied AC adapter)	120V AC, 60Hz, 200mA
Ambient Operating Temperature	0° C - +40° C (32°F - 104°F)
Ambient Operating Humidity	Less than 90% (no condensation)
Compression Methods	JPEG or MPEG-4
Resolution	JPEG: VGA (640 x 480) / QVGA (320 x 240) / QQVGA (160 x 120) MPEG-4: CIF (352 x 288) / QCIF (176 x 144)
Picture Quality	JPEG: Super Fine / Fine / Normal / Low MPEG-4: Fine / Normal / Low
Picture Display Size	x1.0 / x1.5 / x2.0 (resolution does not change)
Interface	10Base-T / 100Base-TX port (RJ-45) x1
Alarm Input	OFF: Open or 4 V DC – 5 V DC ON: Make contact with GND
Alarm Output	Collector output (Internal pull-up) OFF: Open or 5V DC or less ON: 50 mA or less, 1 V DC or less
AUX Output	Collector output (Internal pull-up) OFF: Open or 5V DC or less ON: 50 mA or less, 1 V DC or less
Weight	Approx. 180 g (0.4 lbs.) (AC adapter excluded)
Dimensions	95 mm (H) x 93 mm (W) x 61.5 mm (D) [3.74 in. (H) x 3.66 in. (W) x 2.42 in. (D)] (Wall-mounting bracket excluded)

## STANDARD ACCESSORIES

AC Adapter (Part No. NOJBEP000001) .....	1 pc.
CD-ROM .....	1 pc.
Quick Reference Guide .....	1 pc.
Screw .....	2 pcs.
Wall-mounting Bracket .....	1 pc.